



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.04.2017

Version number 15

Revision: 10.11.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **OEST OECOMIX 2 T**

Article number: 32574

1.2 Relevant identified uses of the substance or mixture and uses advised against
No further relevant information available.

Application of the substance / the mixture fuel

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Georg Oest Mineraloelwerk GmbH & Co. KG

Georg - Oest - Str. 4

D-72250 Freudenstadt

Tel.: +49 (0) 7441 / 539-0

Further information obtainable from:

Tel.: +49 (0) 7441 / 539 - 0

e-mail: productsafety@oest.de

1.4 Emergency telephone number:

Tel.: +49 (0) 7441 / 539 - 0 (08:00 a.m. - 5:00 p.m.) or European emergency call 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 1 H224 Extremely flammable liquid and vapour.



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 4 H413 May cause long lasting harmful effects to aquatic life.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02




GHS07



GHS08

Signal word **Danger**

(Contd. on page 2)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.04.2017

Version number 15

Revision: 10.11.2016

Trade name: OEST OECOMIX 2 T

(Contd. of page 1)

· Hazard-determining components of labelling:

Benzin

· Hazard statements

H224 Extremely flammable liquid and vapour.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P301+P310 IF SWALLOWED: Immediately call a doctor.

P331 Do NOT induce vomiting.

P370+P378 In case of fire: Use for extinction: CO₂, sand, extinguishing powder.

P403+P235 Store in a well-ventilated place. Keep cool.

· 2.3 Other hazards**· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****· 3.2 Chemical characterisation: Mixtures****· Description:** Mixture of substances listed below with nonhazardous additions.**· Dangerous components:**

CAS: 64741-64-6 EINECS: 265-066-7 Index number: 649-274-00-9 Reg.nr.: 01-2119485026-38	Naphtha (petroleum), full-range alkylate ⚠ Flam. Liq. 1, H224; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	50-100%
CAS: 78-78-4 EINECS: 201-142-8 Index number: 601-006-00-1 Reg.nr.: 01-2119475602-38	isopentane ⚠ Flam. Liq. 1, H224; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336	10-<25%

· Additional information:

Conform to the Swedish standard SS 155461: benzene (CAS 71-43-3) < 0,1 Vol.%, hexane (CAS 110-54-3) < 0,5 Vol.%, aromatic compounds < 0,5 Vol.%, olefins < 0,5 Vol.%.

For the wording of the listed hazard phrases refer to section 16.


SECTION 4: First aid measures**· 4.1 Description of first aid measures****· General information:** Immediately remove any clothing soiled by the product.**· After inhalation:** In case of unconsciousness place patient stably in side position for transportation.**· After skin contact:** Immediately wash with water and soap and rinse thoroughly.**· After eye contact:** Rinse opened eye for several minutes under running water.**· After swallowing:**

Aspiration hazard!

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.04.2017

Version number 15

Revision: 10.11.2016

Trade name: OEST OECOMIX 2 T

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
In case of fire, the following can be released:
Carbon monoxide (CO)
Builds slippery and with water smeary coatings
The vapors of this product are heavier than air. They could concentrate on the floor, in caverns, channels and basements and inflame again.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
wear appropriate protective clothing
- **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep away from heat and direct sunlight.
Use only in well ventilated areas.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect from heat.
Protect against electrostatic charges.
Do not spray onto a naked flame or any incandescent material.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.04.2017

Version number 15

Revision: 10.11.2016

Trade name: OEST OECOMIX 2 T

(Contd. of page 3)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Follow TRGS 510
Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Storage class:** 3A
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

64741-64-6 Naphtha (petroleum), full-range alkylate

MAK (Germany)	vgl.Abschn.Xb
---------------	---------------

78-78-4 isopentane

WEL (Great Britain)	Long-term value: 1800 mg/m ³ , 600 ppm
---------------------	---

AGW (Germany)	Long-term value: 3000 mg/m ³ , 1000 ppm 2(II);DFG, EU
---------------	---

IOELV (EU)	Long-term value: 3000 mg/m ³ , 1000 ppm
------------	--

· **DNELs**

78-78-4 isopentane

Oral	DNEL longterm, systemic effect	214 mg/kg (General population)
Dermal	DNEL longterm, systemic effect	432 mg/kg (Workers) 214 mg/kg (General population)
Inhalative	DNEL longterm, systemic effect	3000 mg/m ³ (Workers) 643 mg/m ³ (General population)

- **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Avoid contact with the eyes and skin.

· **Respiratory protection:**

- Use suitable respiratory protective device in case of insufficient ventilation.
- Filter AX

· **Protection of hands:**



Protective gloves

- **Material of gloves** Nitrile rubber, NBR

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.04.2017

Version number 15

Revision: 10.11.2016

Trade name: OEST OECOMIX 2 T

(Contd. of page 4)

· Penetration time of glove material

longterm contact:

NBR: thickness:0,425 mm; break trough: 240 - 480 min.

shortterm contact:

NBR: thickness 0,12; break trough: 10 - 30 min.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses

· Body protection: Protective work clothing**SECTION 9: Physical and chemical properties****· 9.1 Information on basic physical and chemical properties****· General Information****· Appearance:****Form:** Fluid**Colour:** Green**· Odour:** Characteristic**· Odour threshold:** Not determined.**· pH-value:** Not determined.**· Change in condition****Melting point/Melting range:** Undetermined.**Boiling point/Boiling range:** <35 °C (DIN 51751)**· Flash point:** <-18 °C (DIN ISO 2592)**· Flammability (solid, gaseous):** Not applicable.**· Ignition temperature:****Decomposition temperature:** Not determined.**· Self-igniting:** Product is not selfigniting.**· Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.**· Explosion limits:****Lower:** 1.4 Vol %**Upper:** 7.6 Vol %**· Vapour pressure:** Not determined.**· Density:** 0.685 g/cm³ 15 °C (DIN 51757)**· Relative density** Not determined.**· Vapour density** Not determined.**· Evaporation rate** Not determined.**· Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

(Contd. on page 6)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.04.2017

Version number 15

Revision: 10.11.2016

Trade name: OEST OECOMIX 2 T

(Contd. of page 5)

- | | |
|--|--|
| · Viscosity:
Dynamic: | Not determined. |
| · Solvent content:
VOC (EC) | 97.50 % |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with strong oxidising agents.
- **10.4 Conditions to avoid** Avoid naked flames and other ignition sources.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:**64741-64-6 Naphtha (petroleum), full-range alkylate**

Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
Dermal	LD50	> 2000 mg/kg (rabbit) (fixed dose procedure)
Inhalative	LC50	> 5020 mg/l (rat) (OECD 403)

78-78-4 isopentane

Oral	LD50	> 2000 mg/kg (rat) (fixed dose procedure)
------	------	---

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Toxicokinetics, metabolism and distribution** No further relevant information available.
- **Repeated dose toxicity** No further relevant information available.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
No further relevant information available.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.

GB

(Contd. on page 7)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.04.2017

Version number 15

Revision: 10.11.2016

Trade name: OEST OECOMIX 2 T

(Contd. of page 6)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

EC50	> 100 mg/l (algae) (OECD 201)
	> 100 mg/l (daphnia) (OECD 202)
	> 100 mg/l (fish) (OECD 203)
NOEC	100 mg/l (algae) (OECD 201)
	100 mg/l (daphnia) (OECD 202)
	100 mg/l (fish) (OECD 203)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential

Due to the distribution coefficient n-octanol/water a worth-mentioning accumulation in organisms is not expected.

log Pow	0.92 (-) (OECD 107)
---------	---------------------

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

13 07 02*	petrol
15 01 02	plastic packaging
15 01 10*	packaging containing residues of or contaminated by hazardous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA UN1203

14.2 UN proper shipping name

ADR 1203 GASOLINE
IMDG, IATA GASOLINE

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.04.2017

Version number 15

Revision: 10.11.2016

Trade name: OEST OECOMIX 2 T

(Contd. of page 7)

· 14.3 Transport hazard class(es)
· ADR, IMDG, IATA


· Class	3 Flammable liquids.
· Label	3

· 14.4 Packing group

· ADR, IMDG, IATA	II
--------------------------	----

· 14.5 Environmental hazards:	Not applicable.
--------------------------------------	-----------------

· 14.6 Special precautions for user	Warning: Flammable liquids.
--	-----------------------------

· Danger code (Kemler):	33
--------------------------------	----

· EMS Number:	F-E,S-E
----------------------	---------

· Stowage Category	E
---------------------------	---

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
--	-----------------

· Transport/Additional information:
· ADR

· Limited quantities (LQ)	1L
----------------------------------	----

· Excepted quantities (EQ)	Code: E2
-----------------------------------	----------

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· Transport category	2
-----------------------------	---

· Tunnel restriction code	D/E
----------------------------------	-----

· UN "Model Regulation":	UN 1203 GASOLINE, 3, II
---------------------------------	-------------------------

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
· Directive 2012/18/EU
· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5a FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 10 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 50 t

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:
· Information about limitation of use: Employment restrictions concerning juveniles must be observed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H224 Extremely flammable liquid and vapour.

(Contd. on page 9)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.04.2017

Version number 15

Revision: 10.11.2016

Trade name: OEST OECOMIX 2 T

(Contd. of page 8)

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· **Department issuing SDS:** productsafety@oest.de

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 1: Flammable liquids – Category 1

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

· *** Data compared to the previous version altered.**